

SRA3 Colour MFP

MP C4503(A)SP
MP C5503(A)SP
MP C6003SP

✓ Copier ✓ Printer ✓ Facsimile ✓ Scanner



MP C4503(A)SP

45
ppm
B/W
Colour

MP C5503(A)SP

55
ppm
B/W
Colour

MP C6003SP

60
ppm
B/W
Colour

MP C4503(A)SP/MP C5503(A)SP/MP C6003SP

MAIN SPECIFICATIONS

GENERAL

Warm-up time:	20/17/17 seconds
First output speed:	Full colour: 5.7/4.5/4.5 seconds B/W: 4/3.1/3.1 seconds
Continuous output speed:	Full colour: 45/55/60 pages per minute B/W: 45/55/60 pages per minute
Memory:	Standard: 2 GB 2 GB
HDD:	250 GB
Dimensions (W x D x H):	587 x 685 x 963 mm
Weight:	100/100/100.5 kg
Power source:	220 - 240 V, 50/60 Hz

COPIER

Copying process:	Dry electrostatic transfer system
Multiple copying:	Up to 999 copies
Resolution:	600 dpi
Zoom:	From 25% to 400% in 1% steps

PRINTER

Printer language:	Standard: PCL5c, PCL6, XPS, PDF direct print, Mediaprint (JPEG/TIFF) Option: Adobe® PostScript® 3™, IPDS, PictBridge
Print resolution:	Maximum: 1,200 x 1,200 dpi
Interface:	Standard: USB 2.0, SD slot, Ethernet 10 base-T/100 base-TX, Ethernet 1000 Base-T Option: Bi-directional IEEE 1284, Wireless LAN (IEEE 802.11a/b/g/n), Bluetooth
Network protocol:	Standard: TCP/IP (IP v4, IP v6) Option: IPX/SPX
Windows® environments:	Windows® XP, Windows® Vista, Windows® 7, Windows® 8, Windows® Server 2003, Windows® Server 2008, Windows® Server 2008R2, Windows® Server 2012
Mac OS environments:	Macintosh OS X Native v10.5 or later
UNIX environments:	UNIX Sun® Solaris, HP-UX, SCO OpenServer, RedHat® Linux, IBM® AIX
Novell® Netware® environments:	v6.5
SAP® R/3® environments:	SAP® R/3®
Other supported environments:	NDPS Gateway, AS/400® using OS/400 Host Print Transform

SCANNER

Scanning speed:	Full colour: Maximum 80 originals per minute B/W: Maximum 80 originals per minute
Resolution:	Maximum: 1,200 dpi
Original size:	A3, A4, A5, B4, B5
Bundled drivers:	Network TWAIN
Scan to:	E-mail: SMTP, POP, IMAP4 Folder: SMB, FTP, NCP

FAX

Circuit:	PSTN, PBX
Compatibility:	ITU-T (CCITT) G3
Resolution:	Standard: 8 x 3.85 line/mm, 200 x 100 dpi, 8 x 7.7 line/mm, 200 x 200 dpi Option: 8 x 15.4 line/mm, 400 x 400 dpi, 16 x 15.4 line/mm, 400 x 400 dpi G3: 2 second(s)
Transmission speed:	Maximum: 33.6 Kbps
Modem speed:	1 second(s)
Scanning speed:	Standard: 4 MB Maximum: 28 MB
Memory capacity:	

PAPER HANDLING

Recommended paper size:	SRA3, A3, A4, A5, A6, B4, B5, B6
Paper input capacity:	Maximum: 4,700 sheets
Paper output capacity:	Maximum: 3,625 sheets
Paper weight:	52 - 300 g/m²

ECOLOGY

Power consumption:	Maximum: 1,850 W Ready mode: 110 W Low power mode: 69.4 W Sleep mode: 0.67/0.67/0.69 W TEC (Typical Electricity Consumption): 1,927/2,664/2,870 W/h
--------------------	---

SOFTWARE

Standard:	SmartDeviceMonitor, Web SmartDeviceMonitor®, Web Image Monitor
Optional:	GlobalScan NX, Card Authentication Package, Unicode Font Package for SAP, Remote Communication Gate S Pro

OPTIONS

ADF handle, 1 x 550-sheet paper tray, 2 x 550-sheet paper tray, 2,000-sheet large capacity tray, 1,500-sheet side large capacity tray, Bridge unit, 1,000-sheet finisher, 3,000-sheet finisher, Internal finisher, 1,000-sheet booklet finisher, 2,000-sheet booklet finisher, Punch kit for 1,000-sheet finisher, Punch kit for 2,000-sheet finisher, Punch kit for booklet finisher, Internal shift tray, One-bin tray, Side tray, Caster table, Cabinet, Bi-directional IEEE 1284, Bluetooth, Netware, Browser unit, Counter interface, File format converter, Key counter bracket, Card reader bracket, Copy Data Security Unit, Fax Connection Unit, 2nd Super G3 port, Fax option, Wireless LAN (IEEE 802.11a/g/n), SRA3 unit

For availability of models, options and software, please consult your local Gestetner supplier.



Gestetner

www.gestetner.com

ISO9001 certified, ISO14001 certified, ISO27001 certified

All brand and/or product names are trademarks of their respective owners.

Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear.

Copyright © 2013 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.